


9600E FEATURES

Napoleon's 9600E Series is one of the most stylish and efficient furnaces on the market. It's Energy Star rated and performs with higher energy efficiencies, achieving your heating needs with less impact on our environment. The 9600E Series runs using the first, low-fire stage for greater efficiency throughout the heating season. During colder days, the furnace automatically switches to the high fire, second stage to produce additional heat for your home, as if there's two furnaces in one.










VARIABLE SPEED MOTOR



UV LAMP CAPABLE



9600E SPECIFICATIONS

ALL UNITS ARE ENERGY STAR VERSION 4.0 • 95+ AFUE • AMACF ELECTRIC RATING • 2% OR LESS CABINET AIRFLOW LEAKAGE

HEATING CAPACITIES	NEVO40T2A	NEVO60T3A	NEVO80T3A	NEVO8OT4A	NEV100T5A	NEV120T5A
Input (High fire) BTU/hr 0-4500'	38,000	58,000	77,000	80,000	100,000	120,000
Input (Low fire) BTU/hr 0-4500'	25,540	40,600	53,900	56,000	70,000	84,000
CABINET DIMENSIONS (INCHES)	NEVO4OT2A	NEVO60T3A	NEV080T3A	NEVO80T4A	NEV100T5A	NEV120T5A
Width (in)	17 1/2	17 1/2	17 1/2	22 1/2	22 1/2	22 1/2
Depth (in)	29 1/2	29 1/2	29 1/2	29 1/2	29 1/2	29 1/2
Height (in)	32 7/8	32 7/8	32 7/8	32 7/8	32 7/8	32 7/8
VENTING *	NEVO4OT2A	NEVO60T3A	NEVO8OT3A	NEV080T4A	NEV100T5A	NEV120T5A
Clearances to Combustibles	0	0	0	0	0	0
Minimum Vent Size (in)	1 1/2	2	2	2	3	1 1/2
Maximum Vent Size (in)	3	3	3	3	3	2
Minimum Vent Length (ft)	15	15	15	15	15	15
Maximum Vent Length (ft)	100	100	100	100	100	75
AIRFLOW AND COOLING	NEVO4OT2A	NEVO60T3A	NEV080T3A	NEVO80T4A	NEV100T5A	NEV120T5A
Motor Type and Size EON	1/3 hp	1/2 hp	1/2 hp	3/4 hp	3/4 hp	1 hp
AC Tonnages	1 1/2, 2, 2 1/2	1 1/2, 2, 2 1/2, 3	2, 2 1/2, 3	3, 4	2, 3, 4, 5	2, 3, 4, 5



24 Napoleon Road, Barrie, Ontario, Canada L4M 0G8 103 Miller Drive, Crittenden, Kentucky, USA 41030 7200 Trans Canada Highway, Montreal, Quebec, Canada H4T 1A3 Tel: 705-721-1212 napoleonheatingandcooling.com



